S301 INDOOR LED LINEAR

High-output LEDs designed for illumination of shelves, inside counters and cabinets, and architectural backlighting. Simple plug-together connections reduce time and cost of installation, eliminating errors on work site.



LED

12V DC

50 Lm

LED

12V DC

150 Lm

120°

16.5W

9 Lm/W

120°

5.5W

9 Lm/W

KIT-S301-LED12-A

12" Indoor LED Linear **Lighting Strip Kit LED**: 3

Dims: 11 5%" L × 1 34" W × 34" H Includes: (1) S301 Fixture

(1) Direct Connector (1) Power Supply Housing: Aluminum Alloy

Lens: Frosted PMMA Lamp Life: 35,000 hrs Environment: Indoor, Dry

Model	Length	CCT
KIT-\$301	LED12-A 12"	30 3000K
		60 5000K



24" Indoor LED Linear

Lighting Strip Kit LED: 6

Dims: 22 3/4" L × 1 3/4" W × 3/4" H Includes: (1) S301 Fixture

(1) Power Supply

Lens: Frosted PMMA Lamp Life: 35,000 hrs Environment: Indoor, Dry

Model	Length	CCT
KIT-\$301	LED24-A 24"	30 3000K
		60 6000K



KIT-S301-LED24-A LED

(1) Direct Connector

Housing: Aluminum Alloy





KIT-S301-LED36-A

36" Indoor LED Linear **Lighting Strip Kit**

IFD: 9 **Dims**: 33 3/4" L × 1 3/4" W × 3/4" H Includes: (1) S301 Fixture

(1) Direct Connector (1) Power Supply

Housing: Aluminum Alloy Lens: Frosted PMMA Lamp Life: 35,000 hrs Environment: Indoor, Drv

Model	Length	ССТ
KIT-\$301	LED36-A 36"	30 3000K
		60 6000K

KIT-S301-LED48-A

48" Indoor LED Linear **Lighting Strip Kit**

LED: 12

Dims: 44 3/4" L × 1 3/4" W × 3/4" H Includes: (1) S301 Fixture (1) Direct Connector

(1) Power Supply Housing: Aluminum Alloy

Lens: Frosted PMMA Lamp Life: 35,000 hrs Environment: Indoor, Drv

Model	Length	ССТ
KIT-S301	LED48-A 48"	30 3000K
		60 6000K

APPLICATIONS

- Retail, residential, office shelves
- Restaurant and bar displays
- Restaurant wine racks
- Museum artifacts
- Hotel decorative piece accent
- Jewelry store counters
- Office product and award display
- Kitchen and bath, in and undercabinet
- Residential and commercial closet spaces, kitchens and baths
- Decorative backlighting in both residential and commercial applications
- Exhibition and trade show booths
- Safety and security applications

ACCESSORIES TO CONNECT MULTIPLE FIXTURES



120°

11W

9 Lm/W

12V DC

100 Lm

LED

12V DC

200 Lm

120°

22W

9 Lm/W

S301LED-CC06 6" Cable Connector \$301LED-CC12 12" Cable Connector \$301LED-CC24 24" Cable Connector \$301LED-CC36 36" Cable Connector (Sold separately)



\$301LFD-DC1 Direct Connector Directly Connects any 2 Strips. (One included in each Kit).

OPTIONAL CABLES

Model #	Description
S301LED-CC06	6" Connecting Cable
\$301LED-CC12	12" Connecting Cable
S301LED-CC24	24" Connecting Cable
S301LED-CC36	36" Connecting Cable
S301LED-DC1	Direct Connector
DL-PS-2Y	2-Way Split Power Feed
DL-PS-3Y	3-Way Split Power Feed
DL-PS-EXT48	48" LED Driver Extension Cable
DL-PS-EXT96	96" LED Driver Extension Cable

Note: Wattage of linked Fixtures cannot exceed 30W.

