

Project:			
Fixture Type:			
Location:			

Planck LED

Ceiling cord Mounted • Damp Location Listed PROGRESS LED

Contact:

Description:

Provide a dramatic architectural lighting design to any space with this LED pendant. A smooth metal beam with a black finish suspends from the ceiling to add clean visual interest to minimalist residential or commercial settings. The frame holds a polycarbonate shade in place to complete the design.

Specifications:

- · White polycarbonate Diffuser
- The frame holds a polycarbonate shade in place to complete the design.
- A smooth metal beam with a black finish suspends from the ceiling to add clean visual interest to minimalist residential or commercial settings.
- · Provide a dramatic architectural lighting design to any space.
- · Ideal for any hallway, foyer, kitchen, or dining room.
- · Perfect for transitional, modern, or contemporary settings.
- · Measures 47-1/4-inch width by 1-3/8-inch height.
- · Uses one integrated LED that is included (39w max).
- · Compatible with many Triac/ELV dimmers (see dimming controls)
- · Includes installation instructions and mounting hardware.
- · Progress Lighting products are designed for exceptional quality, reliability, and functionality.
- · Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" recessed outlet box: 21.5 in W., 4.75 in ht., 1.25 in depth
- · Mounting backplate for outlet box included
- 108 in of wire supplied

Performance:

Number of Modules	1		
Input Power	39 W		
Input Voltage	120 V		
Input Frequency	60 Hz		
Lumens/LPW (Delivered)	2,900/74 (LM-79)		
ССТ	3000 K		
CRI	90 CRI		
Life (hours)	50000 (L70/TM-21)		
EMI/RFI	FCC Title 47, Part 15, Class B		
Warranty	5-year Limited Warranty		
Labels	cETLus Damp Location Listed		
	Meets California Title 24 JA8-2016		

P500276-031-30



Dimensions:

Width: 47-1/4 in Height: 1-3/8 in Depth: 1-3/4 in

Overall Ht. W/Wire: 113 in

White polycarbonate Diffuser

Width: 46-7/16 in Height: 0-1/16 in



Planck LED

Ceiling cord Mounted • Damp Location Listed PROGRESS LED

P500276-031-30

Dimming Notes:

P500276-031-30 is designed to be compatible with many Triac/Forward Phase controls

The following is a partial list of known compatible dimmer controls.

Dimming Controls:

Leviton 6672

Lutron NTEVL-300

Lutron DVELV-300P

Lutron DVCL-253P

Lutron Caseta Wireless

Lutron AYCL-153P

Lutron TGCL-153-PH-WH

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.