

LUCA

40385BLK-CML

LARGE CONVERTIBLE DRUM

Luca's coastal vibe is permeated with a slightly exotic edge. The bold pendant showcases a robust, woven drum shade, and a full finished cluster for plenty of functional light offered in either Black with Black shade, Polished Chrome with Natural shade, or Black with Camel shade. Luca is part of the Lisa McDennon Collection.

| DETAILS | |
|---------------|-------------------------------|
| FINISH: | Black with Camel Rattan shade |
| MATERIAL: | Steel |
| SHADE: | Camel |
| SLOPE DEGREE: | 90 |

| DIMENSIONS | |
|----------------|-------|
| WIDTH: | 38" |
| HEIGHT: | 14.5" |
| WEIGHT: | 5.5 |
| TOP TO OUTLET: | 0 |

| LIGHT SOURCE | |
|---------------|-------------|
| LIGHT SOURCE: | Socket |
| WATTAGE: | 7-60w Cand. |
| VOLTAGE: | 120v |

| MOUNTING | |
|-------------|-----------|
| CANOPY: | 6.5" Dia. |
| LEAD WIRE: | 1 X 120" |
| MAX HEIGHT: | 48.3 |

| SHIPPING | |
|----------------|----|
| CARTON LENGTH: | 41 |
| CARTON WIDTH: | 41 |
| CARTON HEIGHT: | 15 |
| CARTON WEIGHT: | 20 |
| • | |







- This stem hung fixture may be hung on a sloped ceiling
- This fixture includes multiple down stems in various lengths to customize the installation height
 of the fixture, including one 6" stem and two 12" stems.
- Convertible fixture mounts directly to canopy or with a fixture-specific stem or chain that is 6" or less.
- Suitable for use in dry (indoor) locations as defined by NEC and CEC. Meets United States UL Underwriters Laboratories & CSA Canadian Standards Association Product Safety Standards
- The Lisa McDennon Collection offers a striking mix of edgy, sculptural silhouettes that incorporate modern, organic elements and luxe materials, brought to life by her innovative and original point of view.
- Eclectic style that mixes unconventional elements; unique and sophisticated designs that feel modern and vintage at the same time.
- Striking black finish enhances design
- Please refer to Hinkley's Warranty for complete product warranty details; some warranty limitations may apply.



Toll Free: 1 (800) 446-5539